




Electrically isolated base plate
Industrial standard package
Simplified mechanical design, rapid assembly
Pressure contact

**Double Thyristor Module
For Phase Control
MTx-115-36-F**

Mean on-state current	I_{TAV}		115 A	
Repetitive peak off-state voltage	V_{DRM}		3000...3600 V	
Repetitive peak reverse voltage	V_{RRM}			
Turn-off time	t_q		400 μs	
V_{DRM}, V_{RRM}, V	3000	3200	3400	3600
Voltage code	30	32	34	36
$T_j, ^\circ C$	-40...+125			



MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions
ON-STATE				
I_{TAV}	Maximum allowable mean on-state current	A	115	$T_c = 85\text{ }^\circ\text{C}$; 180° half-sine wave; 50 Hz
I_{TRMS}	RMS on-state current	A	180	
I_{TSM}	Surge on-state current	kA	2.5 3.0	$T_j = T_{j\text{ max}}$ $T_j = 25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p = 10\text{ ms}$; single pulse; $V_D = V_R = 0\text{ V}$; Gate pulse: $I_G = 2\text{ A}$; $t_{GP} = 50\text{ }\mu\text{s}$; $di_G/dt \geq 1\text{ A}/\mu\text{s}$
			2.5 3.0	$T_j = T_{j\text{ max}}$ $T_j = 25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p = 8.3\text{ ms}$; single pulse; $V_D = V_R = 0\text{ V}$; Gate pulse: $I_G = 2\text{ A}$; $t_{GP} = 50\text{ }\mu\text{s}$; $di_G/dt \geq 1\text{ A}/\mu\text{s}$
I^2t	Safety factor	$\text{A}^2\text{s}\cdot 10^3$	30 40	$T_j = T_{j\text{ max}}$ $T_j = 25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p = 10\text{ ms}$; single pulse; $V_D = V_R = 0\text{ V}$; Gate pulse: $I_G = 2\text{ A}$; $t_{GP} = 50\text{ }\mu\text{s}$; $di_G/dt \geq 1\text{ A}/\mu\text{s}$
			20 30	$T_j = T_{j\text{ max}}$ $T_j = 25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p = 8.3\text{ ms}$; single pulse; $V_D = V_R = 0\text{ V}$; Gate pulse: $I_G = 2\text{ A}$; $t_{GP} = 50\text{ }\mu\text{s}$; $di_G/dt \geq 1\text{ A}/\mu\text{s}$
BLOCKING				
V_{DRM}, V_{RRM}	Repetitive peak off-state and Repetitive peak reverse voltages	V	3000...3600	$T_{j\text{ min}} < T_j < T_{j\text{ max}}$; 180° half-sine wave; 50 Hz; Gate open
V_{DSM}, V_{RSM}	Non-repetitive peak off-state and Non-repetitive peak reverse voltages	V	3100...3700	$T_{j\text{ min}} < T_j < T_{j\text{ max}}$; 180° half-sine wave; single pulse; Gate open
V_D, V_R	Direct off-state and Direct reverse voltages	V	$0.6 \cdot V_{DRM}$ $0.6 \cdot V_{RRM}$	$T_j = T_{j\text{ max}}$; Gate open
TRIGGERING				
I_{FGM}	Peak forward gate current	A	5	$T_j = T_{j\text{ max}}$
V_{RGM}	Peak reverse gate voltage	V	5	
P_G	Gate power dissipation	W	3	$T_j = T_{j\text{ max}}$ for DC gate current
SWITCHING				
$(di_T/dt)_{crit}$	Critical rate of rise of on-state current non-repetitive ($f = 1\text{ Hz}$)	$\text{A}/\mu\text{s}$	200	$T_j = T_{j\text{ max}}$; $V_D = 0.67 \cdot V_{DRM}$; $I_{TM} = 2 I_{TAV}$; Gate pulse: $I_G = 2\text{ A}$; $V_G = 20\text{ V}$; $t_{GP} = 50\text{ }\mu\text{s}$; $di_G/dt = 2\text{ A}/\mu\text{s}$
THERMAL				
T_{stg}	Storage temperature	$^\circ\text{C}$	-40...+50	
T_j	Operating junction temperature	$^\circ\text{C}$	-40...+125	
$T_{c\text{ op}}$	Operating temperature	$^\circ\text{C}$	-40...+125	
MECHANICAL				
a	Acceleration under vibration	m/s^2	50	

CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions	
ON-STATE					
V_{TM}	Peak on-state voltage, max	V	2.45	$T_j=25\text{ }^\circ\text{C}; I_{TM}=500\text{ A}$	
$V_{T(TO)}$	On-state threshold voltage, max	V	0.95	$T_j=T_{j\text{ max}};$	
r_T	On-state slope resistance, max	m Ω	3.000	$0.5\pi I_{TAV} < I_T < 1.5\pi I_{TAV}$	
I_L	Latching current, max	mA	500	$T_j=25\text{ }^\circ\text{C}; V_D=12\text{ V};$ Gate pulse: $I_G=2\text{ A};$ $t_{GP}=50\text{ }\mu\text{s}; di_G/dt\geq 1\text{ A}/\mu\text{s}$	
I_H	Holding current, max	mA	250	$T_j=25\text{ }^\circ\text{C};$ $V_D=12\text{ V};$ Gate open	
BLOCKING					
I_{DRM}, I_{RRM}	Repetitive peak off-state and Repetitive peak reverse currents, max	mA	70 2.50	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^\circ\text{C}$	$V_D=V_{DRM}; V_R=V_{RRM}$
$(dv_D/dt)_{crit}$	Critical rate of rise of off-state voltage ¹⁾ , min	V/ μs	1000	$T_j=T_{j\text{ max}};$ $V_D=0.67\cdot V_{DRM};$ Gate open	
TRIGGERING					
V_{GT}	Gate trigger direct voltage, max	V	4.00 2.50 2.00	$T_j=T_{j\text{ min}}$ $T_j=25\text{ }^\circ\text{C}$ $T_j=T_{j\text{ max}}$	$V_D=12\text{ V}; I_D=3\text{ A};$ Direct gate current
I_{GT}	Gate trigger direct current, max	mA	400 250 200	$T_j=T_{j\text{ min}}$ $T_j=25\text{ }^\circ\text{C}$ $T_j=T_{j\text{ max}}$	
V_{GD}	Gate non-trigger direct voltage, min	V	0.25	$T_j=T_{j\text{ max}};$ $V_D=0.67\cdot V_{DRM};$	
I_{GD}	Gate non-trigger direct current, min	mA	10.00	Direct gate current	
SWITCHING					
t_{gd}	Delay time, max	μs	3.00	$T_j=25\text{ }^\circ\text{C}; V_D=1500\text{ V}; I_{TM}=I_{TAV};$ $di/dt=200\text{ A}/\mu\text{s};$ Gate pulse: $I_G=2\text{ A}; V_G=20\text{ V};$ $t_{GP}=50\text{ }\mu\text{s}; di_G/dt=2\text{ A}/\mu\text{s}$	
t_q	Turn-off time ²⁾ , max	μs	400	$dv_D/dt=50\text{ V}/\mu\text{s}; T_j=T_{j\text{ max}}; I_{TM}=200\text{ A};$ $di_R/dt=-10\text{ A}/\mu\text{s}; V_R=100\text{ V};$ $V_D=0.67 V_{DRM};$	
THERMAL					
R_{thjc}	Thermal resistance, junction to case				
	per module	$^\circ\text{C}/\text{W}$	0.0950	180° half-sine wave, 50 Hz	
	per arm	$^\circ\text{C}/\text{W}$	0.1900		
	per module	$^\circ\text{C}/\text{W}$	0.0900	DC	
per arm	$^\circ\text{C}/\text{W}$	0.1800			
R_{thch}	Thermal resistance, case to heatsink				
	per module	$^\circ\text{C}/\text{W}$	0.0300		
	per arm	$^\circ\text{C}/\text{W}$	0.0600		
INSULATION					
V_{ISOL}	Insulation test voltage	kV	3.00	Sine wave, 50 Hz; RMS	t=60 sec
			3.60		t=1 sec
MECHANICAL					
M_1	Mounting torque (M6) ³⁾	Nm	6.00	Tolerance $\pm 15\%$	
M_2	Terminal connection torque (M6) ³⁾	Nm	6.00	Tolerance $\pm 15\%$	
m	Weight, max	g	350		

PART NUMBERING GUIDE

MT	3	-	115	-	36	-	A2	H2	-	F	-	N
1	2		3		4		5	6		7		8

1. Thyristor module (MT)
Thyristor – Diode module (MT/D)
Diode – Thyristor module (MD/T)
2. Circuit Schematic:
3. Average On-state Current, A
4. Voltage Code
5. Critical rate of rise of off-state voltage
6. Group of turn-off time ($dv_D/dt=50\text{ V}/\mu\text{s}$)
7. Package Type (M.F)
8. Ambient Conditions:
N – Normal

NOTES

¹⁾ Critical rate of rise of off-state voltage

Symbol of group	A2
$(dv_D/dt)_{crit}, \text{ V}/\mu\text{s}$	1000

²⁾ Turn-off time ($dv_D/dt=50\text{ V}/\mu\text{s}$)

Symbol of group	H2
$t_{qr}, \mu\text{s}$	400

³⁾ The screws must be lubricated



UL certified file-No. E255404